

Chimney Fire Precautions

Release Date: Th12 8, 2020

SACRAMENTO, Calif. – As temperatures fall and you spend more time indoors in front of the fireplace, the last thing you want to think about is the condition of your chimney. Dirty chimneys can cause chimney fires, which damage or destroy homes and injure people.

Clean chimneys don't catch fire. Make sure a professional chimney sweep inspects your solid fuel venting system annually, and sweeps and repairs it whenever needed. Your sweep may have specific maintenance recommendations depending on how you use your fireplace or stove.

Before lighting a fire, make sure it is safe to do so. Be fire smart. Home fires occur more often in winter than in any other season.

The chimney and the flue that lines it are there to carry dangerous gases from the fireplace or wood stove safely out of the home.

What do chimneys do?

Fireplaces and wood stoves are designed to contain wood-fuel fires while providing heat for a home. Chimneys expel the *by-products of combustion* that include smoke, water vapor, gases, unburned wood particles, hydrocarbon, tar fog and assorted minerals. As these substances leave the fireplace or wood stove, and flow up into the relatively cooler chimney, condensation occurs. The resulting residue that sticks to the inner walls of the chimney is called *creosote*.

What is creosote?

Creosote is a black or brown residue that can be crusty and flaky—tar-like, drippy and sticky—or shiny and hardened. All forms are highly combustible. If it builds up in sufficient quantities, and the internal flue temperature is high enough, the result could be a chimney fire.

Conditions that cause the buildup of creosote:



FEMA

Page 1 of 2

Restricted air supply and unseasoned wood encourage the buildup of creosote. To avoid that buildup:

- Do not restrict the air supply:
 - By closing the glass doors.
 - By failing to open the damper wide enough. The longer the smoke is in the flue, the more likely is it that creosote will form.
 - By closing down the stove damper or air inlets on a wood stove too soon or too much.
- Do not burn *unseasoned wood*:
 - So much energy is used initially just to drive off the water trapped in the cells of the logs that it keeps the resulting smoke cooler than if seasoned wood is used.
 - In the case of wood stoves, overloading the firebox with wood in an attempt to get a longer burn time also contributes to creosote buildup.

Fireplace safety:

- Keep a glass or metal screen in front of fireplace to prevent embers or sparks jumping out.
- Do not burn paper in your fireplace.
- Put the fire out before you go to sleep or leave your home.
- Put ashes in a metal container with a lid, outside, at least 3 feet from your home.

Wood stove safety:

- Make sure your stove is 3 feet from anything that can burn.
- Do not burn paper in your wood stove.
- Put the fire out before you go to sleep or leave your home.

For more information and free resources, go online to www.usfa.fema.gov/prevention/outreach/.

###

